

Engineering Parts List

| Item | Qty | QU | Material Code Ref. Document | Rev. | PC | Material Material Cert. | Industrial Standard to be tested to |
|------|-----|----|--------------------------------|------|---|----------------------------|--|
| 0001 | 1 | PC | 14-075071 | 02 | Valve body | E 1.6580 3.2 | 3 U 20 / PED |
| 0002 | 1 | PC | 14-080295 | 00 | Threaded flange 2 1/4"-12UN-2B | E 1.6580 3.2 | 3 U 20 / PED |
| 0003 | 1 | PC | 14-075073 | 02 | Valve stem complete | F 1.2344/WC(TC) 2.2 | |
| 0004 | 2 | PC | 80-053441 | 00 | Metal-O-Ring 60.6 x 2.39 | F VA / SS | SILVER PLATED |
| 0006 | 1 | PC | 14-075072 | 01 | Valve seat | F 1.2767/WC(TC) | |
| 0008 | 1 | PC | 14-076108 | 00 | Connecting nipple | E 1.6580 3.2 | 3 U 20 / PED |
| 0010 | 4 | PC | 14-076517 | 00 | Stud Bolt 1 1/2"-8UN-2A x 225 | F SA 193 GR B7 3.1 | ASME II-A |
| 0011 | 4 | PC | 80-024778 | 00 | heavy hex nut - 1 1/2"-8UN/2B ANSI B 18.2.2 | F SA-194 Gr. 2H 3.1 | ASME II-A |
| 0012 | 4 | PC | 14-076110 | 00 | Disc | E 1.4545 3.1 | UNS S15500 HÄRTE 43 - 47 HRC |
| 0013 | 1 | PC | 14-076111 | 00 | Guide bush | E 1.6580 3.1 | 3 U 20 / PED |
| 0014 | 1 | PC | 14-075074 | 00 | Packing set Ø32 / Ø20 x 60 | F PTFE-Compound | |
| 0015 | 1 | PC | 14-076114 | 01 | Stuffing bush | E CW 308 G | DIN EN 12420 |
| 0016 | 1 | PC | 14-076115 | 00 | Pressure screw with guide bushing | E 1.4545.3 3.2 | 29 U 20 / PED |
| 0017 | 1 | PC | 80-053031 | 00 | Spring lock washer 5/16" regular ASME B 18.21.1 | F SS | |
| 0018 | 1 | PC | 80-053029 | 00 | Hex. screw 5/16"-18 UNC-2A x 1 1/4 ANSI B 18.2.1 | F SA-193 GR B7 3.1 | ASME II-A |
| 0019 | 1 | PC | 14-076118 | 01 | Scale | F VA | |
| 0020 | 1 | PC | 14-074818 | 03 | Lantern | E 1.6580 3.2 | 3 U 20 / PED |

| | | | |
|----------------|-----------|---|--|
| 14-075070 | 03 | HP-Let down valve DN-1 1/4" (2") PN-1600 300°C Seat-Ø16 (5/8") HIP Petrohemija a.d. Pancevo HP Let Down Valve | Person Resp.: ECKHARDT Date: 02.03.2016 Page: 1 of 2 |
| Our Order No.: | 1873293-1 | | |